

PARTNER

CARE . TRUST . RESPONSIBILITY

All in One POS Terminal PT-6515



All in one POS Terminal PT-6515 Features

- Intel® Celeron processor J1900, Elegant, compact fanless design
- Integrated Triple track MSR
- Integrated 80mm Thermal Printer, Choice of Front Paper out of Rear Paper out
- Choice of integrated Customer Display 2x20 VFD or 7" LCD (Option)
- Integrated Dual Display(Optional)
- WLAN, RFID (optional)

High Performance Fanless All in one POS Terminal

Partner Tech is pleased to announce next generation of high performance All-in-One POS terminal PT-6515.

PT-6515 embedded with powerful Intel Celeron processor J1900 fanless design, brings the power to run today's power hunger POS applications.

PT-6515 is not only the solution for small and medium business, the all in one design brings the mobility capability that can fit in with any environment installation.

Its an affordable yet easy to use integrated terminal, which can help small and medium business to serve customer effectively, and keep pace with competitors.

The compact base embedded with 80mm thermal printer, touch screen and integrated customer display, design with attractive appearance and small footprint for counter space saving.

Item	PT-6515
CPU	Intel® Celeron 2.0GHz processor J1900
Chipset	Intel chipset
LCD	15" LCD, resolution 1024 x 768 LED backlight LCD
Touch	Projected Capacitive Touch
Construction	Plastic cover & metal heat sink bottom
Memory	2G up to 8G (DDR3)
Ethernet	Onboard 10/100/1000 BASE-T Gigabit Ethernet
Storage	Internal 2.5" type SATA HDD (optional SATA SSD)
External I/O Interface	4 * COM ports [COM1~4 on rear I/O (COM1~2 powered with DC+0/5/12V, BIOS selection; COM3~4 by Jumper setting) 1 * DB-15 VGA port 1 * DB-25 for LPT port 1 * RJ11 port supports 2 cash drawer(DC+24V) 1 * RJ-45 LAN port with activity and link LEDs 4 * USB 2.0 1 * PS2 Keyboard port 1 * DC +12V input power-jack for adapter
Printer	Front paper out 80mm 180 DPI 180mm/s or Rear Paper out 80mm 203 DPI 250mm/s
MSR	3 tracks magnetic reader
Optional	Integrated Customer display 2 x 20 VFD or CD-70 Dual Pole display RFID WLAN
Operation System	POS Ready7, Windows 7, Windows 8.1 Industry Pro Retail, Linux (Ubuntu)
Power Supply	AC100~240V/DC12V,15A, 180W adapter
Operating Temp	0°C ~ +40°C
Certification	CE, FCC, LVD, VCCI, BSMI, 3C



15" TFT LCD Touch Screen



Integrated Dual Display with Adjustable Pole (option)



Integrated 2 x 20 VFD Integrated 7" LCD (option)



Rear Paper out printer



Front Paper out printer

* specification subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX: +886-2-29153405	E-mail:sales@partner.com.tw
USA	TEL:+1-949-598-1888	FAX: +1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130	E-mail:info@partner-tech.eu
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308	E-mail:sales@partnertechuk.com
China	TEL:+86-21-67696667	FAX: +86-21-67696699	E-mail:sales@partnertech.com.cn
Africa	TEL:+27-11-700-7188	FAX:+27-11-700-7140	E-mail:sales@partnertech.co.za
Middle East	TEL:+971-4-8862980	FAX:+971-4-8862980	E-mail:sales@partnertechme.com
Korea	TEL:+82-10-6404-8223	I-Phone:+82-70-4104-8223	E-mail:adams_c@partner.com.tw

