

**PARTNER**

CARE . TRUST . RESPONSIBILITY

# MP-300

## Mobile Bluetooth Printer



The MP-300 is a 80 mm mobile thermal printer. It has a compact, elegant, light weight design and can read Barcodes as well.

The mobile printer can be used multifunctional and can fit in different environments such as Queue-busting, tableside service, ticketing and field service.

This small mobile printer saves time, improves the service and business.

### **Special Features:**

- 80 mm thermal printer
- Printing speed 60 mm/sec
- Dot density 203 dpi
- 106 mm (W) x 100 mm (D) x 49.5 mm (H)
- Light weight
- Big paper rolls can be used
- Leather holder included
- Bluetooth Class 2

## Mobile Bluetooth Printer MP-300



### Technical data

Printing method	Direct Thermal		
Printing speed	60 mm/sec		
Dot density	203 dpi		
Dot pitch	8 dots/mm 0.125 pitch		
Effective printing	Width: 72 mm, 576 dots/line		
Character per line	Font A (12x24) 48 columns / Font B (9x24) 64 columns		
Paper	Type: Thermal paper Width: 80 mm Thickness: 65 µm Roll diameter: Max. 45 mm Roll core inner diameter: 12.5 mm +- 0.5 mm		
Reliability	TPH life: 50 km, Pulse activation: 100milin pulse or more (12.5% print ration)		
Character set	Extended graphic: 128 x 18 Page (1 space page) International character: 14		
Barcode	EAN-8, EAN-13, CODE39, ITF, UPC-A CODABAR, CODE93, CODE128, PDF417 (2D)		
Emulation	ESC-POS		
Driver	Windows CE 4.2 & 5.0, Windows mobile 5.0		
Sensor	Standard: Paper end sensor, Cover open sensor, Option: Black mark sensor		
Interface	Standard: Bluetooth class 2, Option: IrDA		
Power	Battery: 7.2V 1200mAH Li-ion, 2Hrs Charging Time 40-50 minutes in continuous operation		
Dimension	106 mm (W) x 100 mm (D) x 49.5 mm (H)		
Weight	290 g (with battery)		
Environment	Operating	Storage	
	Temperature:	5~40° C	-20~60° C
	Humidity:	35%~80%	10%~90%
Accessories	Battery, RS-232 cable, charger, paper roll, manual, CD, leather case (option)		
Certifications	CE, FCC, CB, UL, BSMI, CCC RF: NCC, SRRC, FCC ID, R&TTE		

