TM-H6000III





- Ultra-fast printing performance up to 200 mm/sec.
- Higher efficiency with quick printing and endorsement of checks in a single pass.
- Designed for optimum performance and durability in high-volume environments.

SPECIFICATIONS

Terminal Module Hybrid Printer

™-H6000™





Receipt: Thermal line printing, Slip: 9-pin serial impact dot matrix, E / P: 8-pin shuttle impact dot matrix PRINT METHOD

PRINT FONT Font

Receipt: 9 x 17 / 12 x 24, Slip: 5 x 9 / 7 x 9, E / P: 5 x 7 Receipt: 56 / 42, Slip: 45 / 60, E / P: 40 Column Capacity (Columns)

Character Size (mm)

Character Set

E / P: 40

Receipt: 0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H)

Slip: 1.56 (W) x 3.1 (H) / 1.24 (W) x 3.1 (H)

E / P: 1.1 (W) x 2.42 (H

Receipt / Slip: 95 Alphanumeric, 37 International,

Receipt: 128 x 11 Graphic, Slip: 128 x 12 Graphic,

Bar code: UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN8), CODE 39, CODE 93,

CODE 128, ITF, CODABAR, Two-dimensional code: PDF417 (Receipt only)

Characters Per Inch Slip: 13.3 cpi / 17.8 cpi

INTERFACES RS-232, Bi-directional parallel Dealer option: RS-485, USB, 10 Base-T I/F

DATA BUFFER 4 KB / 45 bytes

PRINT SPEED

Receipt: Max. 200 mm / sec. Slip: Approx. 5.7 lps (at 40 columns, 17.8 cpi) E / P: Approx. 1.9 lps

Receipt: Thermal roll paper: 79.5 ± 0.5 (W) x dia. 83.0 Slip & E / P: 68 to 230 x 68 to 297 mm (W x L) Note: The minimum paper size is 68 x 152 mm PAPER Dimensions (mm)

Thickness (mm) Receipt: 0.06 to 0.09, Slip: 0.09 to 0.31 E / P: 0.09 to 0.2

Slip: One original and three copies E / P: One original single ply COPY CAPACITY

INKED RIBBON Slip: ERC-32 (Black), E / P: ERC-41(Black)

RIBBON LIFE Slip: Black: 4,000,000 characters

E / P: Black: 800,000 characters POWER 24 VDC ± 10%

Receipt: Approx. 1.8 A Slip: Approx. 1.7 A POWER CONSUMPTION

D.K.D. FUNCTION 2 drivers

RELIABILITY Receipt: 360,000 hours, Slip: 180, 000 hours Receipt: 72,000,000 lines, Slip: 18,000,000 lines MTBF

OVERALL DIMENSIONS (MM) 186 (W) x 298 (D) x 185 (H)

MASS (APPROX.) 5.3 Kg

EMC STANDARDS VCCI class A, FCC class A, CE marking, AS / NZS 3548

POWER SUPPLY PS-180 (option)

FACTORY OPTIONS MICR device, Endorsement printer (E / P)

SAFETY STANDARDS UL / CSA / EN

EPSON and ESC/POS are registered trademarks of SEIKO EPSON Corporation.

JavaPOS is a trademark of Sun Microsystems, Inc in the U.S. and other countries.

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc and any use of such marks by SEIKO EPSON Corporation is under license. Other trademarks and trade names are those of their respective owners.

All products and brand names herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All images are simulated in this brochure Specifications are subject to change without prior



INDIA - (91) 80-305-15000, CALCUTTA - 228 31589/90, CHENNAI - 302 77500, MUMBAI - 282 61515/16/17,

NEW DELHI - 306 15000 INDONESIA - (62) 21-572-3161 MALAYSIA - (60) 3-562-88288 PHILIPPINES - (632) 706-2663

SINGAPORE - (65) 6586-5500, (65) 6586-3111 THAILAND / INDOCHINA - (662) 685-9888

Dealer's Stamp