

9-pin, serial dot

TM-U325



Versatile Printing

Receipt printing and multi-line validation up to 9 lines from a compact, space-saving unit.

Quiet, Fast Output

Designed for environments where quiet operation is a must. Features logic-seeking control for fast 6.4 lps receipt and multi-line validation printing.

High-Performance 1.25 Station Printer

Print method	9-pin, serial impact dot matrix
Print font	Font 7 x 9 / 9 x 9 Column capacity (columns) 40 / 42 or 33 / 35 (3 half dots / 2 half dots space) Character size (mm) 1.2 (W) x 3.1 (H) / 1.6 (W) x 3.1 (H) Character set 95 Alphanumeric / 32 International, 128 x 8 Graphic Characters per inch 16 or 17.8 cpi / 13.3 or 14.5 cpi
Interfaces	RS-232, Bi-directional parallel, Dealer option: RS-485, USB, 10 Base-T I/F
Data buffer	4 KB or 45 bytes
Print speed	Approx. 3.5 lps (at 40 columns, 16 cpi) Approx. 6.4 lps (at 16 columns, 16 cpi)
Paper	Dimensions (mm) Receipt: 76.0 ± 0.5 (W) x dia. 83.0 Validation: 135 (W) x 70 (L) to 182 (W) x 182 (L) (Maximum print lines: 9 lines) Thickness (mm) Receipt: 0.06 to 0.085 (total thickness: 0.2mm or less) Validation: 0.09 to 0.12 (total thickness 0.09 to 0.31)
Copy capability	One original and two copies
Inked ribbon	ERC-38 (Purple, Black)
Ribbon life	Purple: 4 x 10 ⁶ characters, Black: 3 x 10 ⁶ characters
Power	AC adapter (included)
Power consumption	Approx. 43 W
D.K.D.function	2 drivers
Reliability	MTBF: 18 x 10 ⁴ hours MCBF: 49 x 10 ⁶ lines
Overall dimensions (mm)	164 (W) x 240 (D) x 136 (H)
Mass (Approx.)	2.3 kg
EMC standards	FCC class A
Power supply	Exclusive AC adapter (included)
Safety standards	UL / CSA

