

MOB

POSREADY

## **Be unique** Stylish and flawless POS printers

# 

#### Chic

The CT-S251 is perfect for high class restaurants and boutiques where the environment requires a top class POS printer with eye-catching design. Choose between the white or black versions.

#### Fast

With its unique and stylish design, the twoinch CT-S251 POS printer is perfect for receipt or queue management systems. With a class-leading 300 mm/s print speed, front exit and compact size, the CT-S251 blends performance and poise.

# CITIZEN CT-S251 POS

#### **Applications**

- Receipts
- Queue management
- Weigh scales
- Coupons
- Daily reports
- Hospitality



#### **Well connected**

Connectivity is key with the possibility for USB, Serial, MFi Bluetooth<sup>®</sup>, Ethernet and WiFi interfaces and toolkit support for iOS<sup>™</sup>, Android<sup>™</sup> and Windows<sup>®</sup> operating systems.That creates ideal conditions for easy integration.



**Global** Vision

GLOBAL VISION - Robot Tower, 308-308C Dien Bien Phu St, Ward 3, District 10, HCMC, Vietnam

(84-8) 3818 1866 . (84-8) 3818 1972 . (84-8) 38680104 . http://globalvision.com.vn/ . @GlobalVisionVN



#### Easy to use

Thanks to the robust yet user friendly design, the CT-S251 has quick and efficient paper loading, preventing paper jams.



#### Specifications

Model		CT-S251
Printing method		Line Thermal Dot Printing
Printing width		54mm/432 dots
Dot pitch		8 x 8 dots/mm (203 dpi x 203 dpi)
Number of columns		Up to 36 digits (12 $\times$ 24: font A), Up to 48 digits (9 $\times$ 24: font B), Up to 54 digits (8 $\times$ 16: font C)
Printing speed		Max. 300mm/sec., When greyscale printing: 130mm/sec
Line spacing		4.23mm (1/6 inch); adjustable by user comand
Barcode type		UPC-A, UPC-E, JAN / EAN-8, JAN / EAN-13, ITF, CODE39, CODE93, CODE128, CODABAR (NW-7), PDF417, QR Code, GS1 Databar.
Emulation		ESC/POS™®
Paper	Width	57.5 +/- 0.5mm / 2.26 +/- 0.02in
	Diameter	83mm / 3.27in or less
	Thickness	53µm to 85µm
	Recommended Paper	Mitsubishi Paper Mills P220AG normal type 65, HP220AB-1 highly conserved type 75, F230AA normal type 65, P220AB normal type 85, Oji Paper PD150R normal type 75, PD160R high storage type 65/75, Nippon Paper TF50KR-2Y high storage type 62, TR50KJ-R high-save type 63
Power adapter		37AD2 (AC Adapter)
AC input voltage		AC 100 to 240V, 50/60 Hz, 150 VA
DC operating voltage		24V DC ±7%, supplied by AC adapter
Weight		1.20 Kg / 2.65 lb
Dimension (W x D x H)		108 x 165 x 108 mm +5mm front lip / 4.25 x 6.49 x 4.25 in +0.2in front lip footprint
Operating environment		+5 to 45°C / +41 to 113°F, 10%-90% RH, non condensing
Storage environment		-20 to 60°C / -4 to 140°F, 10%-90% RH, non condensing

All product names are trademarks of the respective manufacturers. ESC/POS<sup>™®</sup> are trademarks or registered trademarks of Seiko Epson Corporation. Bluetooth<sup>®</sup> is a registered trademark of the Bluetooth SIG and WiFi is the registered trademark of the Wi-Fi Alliance. Android<sup>™</sup> is a trademark of Google Inc., IOS<sup>™</sup> is a trademark of Cisco Systems. Windows<sup>®</sup> is either a registered trademark or trademark of Microsoft Corporation.

Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

GLOBAL VISION - Robot Tower, 308-308C Dien Bien Phu St, Ward 3, District 10, HCMC, Vietnam

(84-8) 3818 1866 . (84-8) 3818 1972 . (84-8) 38680104 . http://globalvision.com.vn/ . @GlobalVisionVN

### CITIZEN CT-S251 POS

#### **Features & Benefits**

- Front Exit
- Fast 300 mm/sec
- 2-inch media: 57.5 ± 0.5 mm
- MFi / iOS<sup>™</sup> Bluetooth<sup>®</sup> version
- WiFi and Ethernet versions
- ENERGY STAR<sup>®</sup> power supply
- Stylish black or white case
- Same height as cash drawers
- Cash drawer connection
- ESC/POS<sup>™®</sup> compatibility
- SDKs for iOS<sup>™</sup>, Android<sup>™</sup>, Windows<sup>®</sup>



# **Global** Vision