Epson

TM-T70

Thermal Printer



- Front-facing controls, paper loading and receipt dispensing
- Small, space-saving footprint
- Designed to fit under counters
- Fast and versatile printing up to 170mm per second
- Same fast print speed for both text and graphics
- Ideal for specialty retail, food service, convenience stores and kiosks
- Ease-of-use features including drop-in paper loading, autocutter and status LEDs
- Low power consumption, ENERGY STAR® qualified
- Two-year warranty



The TM-T70, with easy all-front access, is designed to fit under counters.

The innovative, space-saving TM-T70 printer with easy all-front access is the only receipt printer available today that is designed to operate entirely from the front of the printer. This means you can put it under a counter or on a shelf and free up your valuable counter space.

Big performance. Small footprint.

Streamline your POS system with Epson's space-saving TM-T70 printer. With its small size and low height (only 4.49" high), it's designed to fit under your counter or in other small spaces. And it has all the features you need to keep your lines moving.

High-speed, high resolution text and graphics printing

The TM-T70 prints receipts and graphics at the same fast print speed of 170mm/second. And with its 180 dpi resolution you are assured of crisp, clear receipts and eye-catching logos. Barcodes are also supported, including 2D.

Easy to use. Easy to maintain.

You can operate and maintain the TM-T70 entirely from the front of the printer. It features front-dispensing receipts, front drop-in paper loading and front-facing controls.

Reliability you can count on

With a MCBF of 52 million lines, the TM-T70 features the same high reliability of our best-selling TM-T88 printer series. It also has a sealed top for superior spill resistance and an optional cable management system.

Lower energy costs

The TM-T70 features low power consumption to reduce your operating costs and is ENERGY STAR qualified and RoHS compliant.

Integration made easy

With Epson's Connect-It[™] interfaces, the TM-T70 is compatible with today's best-of-breed and component-based systems. Interface options include USB, serial, parallel, Ethernet and wireless.

Find out more

To learn more about Epson's space-saving TM-T70 printer with easy, all-front access, visit our website at pos.epson.com.

Global Vision

Hotline: 0907 669 388

Tel: (84-8) 3868 0104 - Fax: (84-8) 3868 0105 sales@globalvision.com.vn www.globalvision.com.vn

Epson TM-T70 Thermal Printer

Printer Specifications		TM-T70
General	Print method Print font	Thermal line printing
	Font	Font A: 12 (W) x 24 (H) dots Font B: 9 (W) x 17 (H) dots
	Column capacity	42/56 columns
	Character size	1.69 (W) x 3.38 (H) mm / 1.27 (W) x 2.40 (H) mm
	Character set	95 Character Alphanumeric, 48 Character International, 128 x 11 Pages Graphic
	Barcode	6 one-dimensional, 2 two-dimensional
Printer	Interface	RS-232, RS-485, Parallel, USB, Ethernet 10 Base – 100 Base TX, IEEE 802.11b
	Data buffer	4KB or 45 bytes selectable
	Print speed	170 mm/sec, (6.69"/sec)
	Paper dimensions	79.5 ± 0.5 x 83 mm (3.13" ± 0.02" x 3.27")
	Paper diameter	83 mm (3.27" maximum)
	Power	24 Volts DC
	Power consumption	Approx. 1.8A (mean)
	D.K.D. function	2 drivers
	Reliability MTBF	360,000 hours
	MCBF	52,000,000 lines
	Autocutter	1.5 million cuts
	Overall dimensions	4.92" x 7.64" x 4.49"; (125 (W) x 194 (D) x 114 (H) mm)
	Mass	3.97 lb (1.8 kg)
	Color	Epson Dark Gray, Epson Cool White
	Options	Cable management cover OT-CC70, PS-180 AC adapter, shelf bracket, affixing tape and Connect-It interfaces*
	Safety standards	UL/CSA
	EU directive	RoHS and WEEE compliant
	Warranty	Two-year limited warranty

Inch values are approximate. dpi: dots per 25.4mm (dots per inch)



Optional mounting bracket available for positioning printer under counter.











Tel: (84-8) 3868 0104 - Fax: (84-8) 3868 0105 sales@globalvision.com.vn Hotline: 0907 669 388 www.globalvision.com.vn

^{*}To find out more about our line of Connect-It interfaces, contact your Epson Sales Representative.