



RP-500

Receipt Printer

Features At-A-Glance

Roll Thermal Printer

Serial, Parallel or Ethernet Interface

200mm/sec High Speed Printing

Wall Mountable



Specifications

PRINTING

- Direct Thermal
- 200mm/sec
- 72mm (512 Dots/line)
- 180DPI

PAPER

- Thermal Paper
- 58mm – 80mm
- Max. F 83.0mm

RELIABILITY

- 160 km
- 60,000,000 Lines

AUTO CUTTER

- 1,500,000 cuts (guillotine)

SENSOR

- Paper end, cover open, buzzer

INTERFACE

- USB
- Serial or Parallel or Ethernet

WEIGHT

- 3.5 lbs

EMULATION

- ESC/POS Command compatible
- Window Printer driver (7, XP, VISTA), POSReady, OPOS

DRIVER

- Linux, JavaPOS

POWER

- 100-240vAC input, DC+24v output

ACCESSORIES

- Power adaptor
- 58mm paper guide (spacer)
- Wall mount bracket
- QSG

TEMPERATURE

- 41° F – 104° F
- -4° F – -76° F

DIMENSION

- 5.51" x 7.83" x 5.94" (W x D x H)

COLOR

- Black

Features In Detail



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2012 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.