



The RP-600 is a high speed thermal printer for retail and hospitality environments that have efficient, green and adaptable printing needs.

The RP-600 is particularly fast with a printing rate of up to 230 mm/s at a resolution of 180 dpi. Its compact size and high performance make this dependable model absolutely ideal for many applications. The RP-600's variety of character sets can be enlarged 1-6 times both horizontally and vertically will satisfy any text requirement while the option for a watermark can individualize each print. A wide range of interface and port optionsallows for easy installation and simple integration to POS environments and POS solutions.

RP-600

Thermal Receipt Printer



RP-600

Item		RP-600
Printing	Method	DirectThermal
	Speed	230mm/sec
	Width	72mm(512Dots/Line)
	Resolution	180 DPI
Paper	Туре	Thermal Paper
	Width	1.9"~ 3.2"
	Thickness	0.002"~ 0.003"
	Roll Diameter	Max. F 3.15"
	Roll Core Inner	0.49" ± 0.01"
Memory		RAM: 2MB, Flash: 2MB
Reliability	Tph life	150km
	Mcbf	60,000,000 Lines
Auto cutter		1,500,000 cuts(Guillotine)
Sensor	Standard	Paper End, Cover Open Black Mark, Paper near End
Interface	Standard	USB + (Serial, Parallel or Ethernet)
	Option	Serial, Parallel, Ethernet
Emulation		ESC/POS Command Compatible
Driver		Window Printer Driver (7, XP), OPOS, Linux, JavaPOS
Power	Туре	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc /2.15A
Temperature	Operation	5"C ~ 40"C
	Storage	-20°C ~ 60°C
Dimensions		196mm x 146mm x 148mm (L x W x H)
Color		Black, White













^{*} specification subject to change without prior notice