





Innovative Technology for Customer Interaction

Star's Asura CPRNT is a powerful, feature rich interactive communication platform with an integrated high-speed printer. At its heart is a reliable ARM processor that manages a seven-inch touch screen and a three-inch printer. The Asura CPRNT is available with optional integrated MSR, 2D imager modules. The Asura CPRNT's computing power offers the capability to display and deliver audiovisual messages on its own screen as well as on external signage. The Asura CPRNT also has the ability to drive content to digital devices such as smart phones, merchant tablets and digital signage. The Asura CPRNT has been optimized to support connection of external peripherals such as a biometric scanner, WiFi/3G/4G dongle, camera and many others.

Interactive



View advertisments, apps and stream web content to create an unrivaled customer experience.

Connected



Connect to phones, tablets and other mobile devices.

Integrated



Optional integrated MSR and 2D imager.













7" LCD Touch Screen

Touch Panel Specifications: 800x480 pixel TFT Resistive LCD



Compact Size, Huge Capabilities

Compact footprint for user counter / shelf / kiosk integration



LED Lighting 3 basic color LED

Lighting for multicolor programmable visual feedback.



Magnetic Stripe Reader / 2D Imager Swipe credit cards with ease!



AsuraCPRNT

AsuraCPRNT Specifications

Features: Integrated High-speed 3" (80mm) Printer with Auto Cutter

Swivel and Tilt 7" LCD touch screen

ARM Based CPU

High quality and fast print speed 32 level grayscale printing Internal power supply Electronic lock function Internal Speaker Black Mark Support

LED lighting for visual feedback VESA back mount supported

Connectivity: USB-Host x 4 (Type A)

USB-Device x 1 (Type B)

Audio Line Out MIC Input

Ethernet (100/10 Base T)

Micro SDHC Drawer Kick

Operating System Option: Linux Angstrom Kernel 2.6.x

Android (by special request)

Optional Accessories: Magnetic Stripe Reader

2D Imager

What's Included: Base Stand

Power Cable Paper Guide

Technical Specifications: Touch Panel: 7" (800x480 pixel) TFT Resistive LCD

CPU: ARM Cortex-A8 Core Memory: 256MB DDR2 Print Method: Direct Thermal Print Speed: 300 mm/s Grayscale: 8 / 16 / 32 bit Paper Width: 58 / 65 / 80mm Paper Thickness: 0.053- 0.085 mm Paper Diameter: max 83 mm Black Mark Sensor Supported

Dimension: (W)180mm X (D)162mm X (H)380mm

Part Number: 36940110

For further information:

 Sales
 1-855-809-2010

 Technical Support
 1-800-782-7636

 Web
 www.starmicronics.com

5/13/13

