

Reliability, Convenience, Intelligence.

Single Sided Color Card Printer Optimized for Fast Color Printing with i Series Intelligence and Convenience.

The Eltron P310i is an intelligent, reliable, single sided color card printer with new convenient features for ease-of-use while producing superior quality printing at an affordable price. Quiet operation and small footprint make it ideal for desktop and reception area printing.



Eltron P310i Advantages

Advanced Color Printing: Enhanced color-processing firmware, new richer ribbon color formulation, optimized for printing photo identification badges and membership cards

Operator Convenience: Easy-to-use "load and go" ribbon system, automatic driver configuration, ribbon low notification, quick reference Operator Help Guide, Windows® 98, ME, NT, 2000 and XP printer drivers with install wizard

Reliable Operation: Based on the highly reliable, field-proven P310 print engine

Basic Specifications:

- 25 Seconds/Card Print Speed
- 300 dpi
- Full Color Single Sided Card Printing
- Parallel, Serial or USB Interface
- 75 Card Capacity Feeder
- i Series Printers require the use of i Series ribbons for full color printing

i series Printers **Eltron i Series: Intelligent Printing System**

The P310i also features the benefits of enhanced i Series functionality. Eltron i Series printers are designed to make card printing a simple function for all users. The system features:

- Advanced RFID Technology
- Automatic Driver Configuration
- Intelligent Color Optimization
- Ribbon Image Counter & Ribbon Low Notification
- Enhanced Ribbon Formulation



Eltron® P310i

General Specifications

- High speed printing
- 144 cards/hour for color, single side (YMCKO)
- 900 cards/hour for resin black (K)
- 2MB image memory standard
- Windows drivers for 98, NT, 2000, ME, XP
- One year printer warranty
- One year (unlimited passes) printhead warranty*

Color Printing

- Color dye sublimation or monochrome thermal transfer printing
- 25 seconds per card full color single sided (YMCKO)
- 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- Code 39, Code 128 B & C with & without check digit
- 2 of 5 & 2 of 5 Interleave
- UPC-A, EAN 8 & EAN 13
- PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- Resident: Arial
- True Type fonts via Windows driver

Card Specifications

- Types: PVC, composite
- Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- Magnetic Stripe-ISO 7811
- Smart Card-ISO 7816-2
- Card Thickness: 10 mil (.25mm) to 60 mil (1.524mm)
- Card feeder capacity: 75 cards (30 mil)
- Card output hopper capacity 75 cards (30 mil)

Ribbon Specifications

- i Series Printers require the use of i Series ribbons for full color printing
- Monochrome: 1500 and 1000 cards/roll
- K Resin + O: 500 cards/roll
- YMC: 300 cards/roll
- YMCK: 400 cards/roll
- YMCKO: 330 cards/roll
- Overlay varnishes: clear and hologram



Communications Interface

- Centronics parallel (parallel cable included)
- USB option 
- Serial option

Mechanical

- Width: 12.4 in (315mm)
- Depth: 7.75 in (198mm)
- Height: 8.7 in (220mm)
- Weight: 13.4 lbs (6.1kg)

Electrical

- 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- FCC Class B, CE, UL and CUL approved

Environmental

- Operating temperature: 60°F to 86°F (15°C to 30°C)
- Operating humidity: 20% to 65% non-condensing
- Storage temperature: -23°F to 158°F (-5°C to 70°C)
- Storage humidity: 20% to 70% non-condensing
- Ventilation: Free air

Options

- Smart card contact station (30 mil cards only)
- USB interface
- Serial interface
- Magnetic encoder (30 mil cards only)
- Extended warranty program
- Hot Swap warranty program
- Cleaning supplies
- Service manual

* For optimum performance, use Zebra/Eltron approved media.

Eltron® www.eltroncards.com



Zebra Technologies Corporation



© 2002 Zebra Technologies Corporation.
All Rights Reserved. Specifications subject to change without notice. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P310i-10/02

American Operations

Zebra Technologies Corporation
1001 Flynn Road
Camarillo, CA 93012-8706
United States of America
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@eltron.com

European Headquarters

Zebra Technologies Corporation
Zebra House
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@eltron.com

Asia Pacific Headquarters

Zebra Technologies Corporation
1 Sims Lane #06-11
387355 Singapore
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@eltron.com