



### General Purpose Corded Handheld Area Imager Bar Code Reader

The Gryphon™ 4000 series represents the premium level of data collection devices from Datalogic Scanning for general purpose applications. Designed with people in mind, the Gryphon™ I GD4400 imager blends advanced 2D reading with motion sensing technology, producing a user-friendly device with outstanding performance.

Perfect for both handheld and presentation reading, the Gryphon I GD4400 imager features Datalogic's Motionix™ motion-sensing technology which detects the natural actions of the operator to automatically switch the scanner into the desired scanning mode. This technology works with or without the use of a stand, offering more operational choices. Both the aimer and sensor can be programmed to the user's desired preferences.

User comfort is maximized with the Gryphon I GD4400 imager's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces

accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

The Gryphon I GD4400 imager provides snappy reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. High Density (HD) models are also available for reading smaller, condensed codes. For mobile marketing or ticketing applications, this imager also offers excellent performance when reading bar codes from mobile devices.

The Gryphon I GD4400 2D omnidirectional reader eliminates the need for separate equipment with signature capture and document scanning capabilities. Its enhanced optics offer improved motion tolerance and high speed imaging to read fast moving codes.

As a corded device, the Gryphon I GD4400 imager is available in two different interface models: a multi-standard interface for connection to the host via USB (COM and Wedge Emulation), RS-232 or Wedge Emulation or an IBM 46XX interface model, including USB and RS-232 interfaces.

### Features

- Motionix™ motion-sensing technology for seamless reading mode transitions
- Highly visible 4-Dot aimer with center cross for targeted scanning
- Omnidirectional reading
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads 1D, 2D and postal codes plus stacked and composite codes
- Multi-interface options: RS-232 / IBM 46XX / USB or RS-232 / USB / Keyboard Wedge / Wand
- Datalogic's patented 'Green Spot' for good-read feedback



## Specifications

### DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.

2D CODES

Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code

POSTAL CODES

Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)

STACKED CODES

EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

### ELECTRICAL

CURRENT

Operating (Typical): GD4410: < 170 mA @ 5 VDC; GD4430 < 160 mA @ 5 VDC

INPUT VOLTAGE

Standby/Idle (Typical): 65 mA @ 5 VDC  
GD4410: 4.0 - 14.0 VDC; GD4430: 4.2 - 5.25 VDC

### ENVIRONMENTAL

AMBIENT LIGHT  
DROP RESISTANCE

0 - 100,000 lux  
Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface.

ESD PROTECTION (AIR DISCHARGE)  
HUMIDITY (NON-CONDENSING)  
PARTICULATE AND WATER SEALING  
TEMPERATURE

16 kV  
5 - 95%  
IP52  
Operating: 0 to 50 °C / 32 to 122 °F  
Storage/Transport: -20 to 70 °C / -4 to 158 °F

### INTERFACES

GD4410: RS-232 / IBM 46XX / USB Multi-Interface  
GD4430: RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

### PHYSICAL CHARACTERISTICS

COLORS AVAILABLE  
DIMENSIONS  
WEIGHT

Black; White  
18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in  
195.0 g / 6.9 oz

### READING PERFORMANCE

IMAGE CAPTURE  
IMAGER SENSOR  
LIGHT SOURCE  
MOTION TOLERANCE  
PRINT CONTRAST RATIO (MINIMUM)  
READING ANGLE  
READING INDICATORS  
RESOLUTION (MAXIMUM)

Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2  
Wide VGA: 752 x 480 pixels  
Aiming: 650 nm VLD  
25 IPS  
25%  
Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°  
Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED  
**High Density (HD):** 1D Linear: 0.077 mm / 3 mils;  
Data Matrix: 0.127 mm / 5 mils; PDF417: 0.102 mm / 4 mils  
**Standard Range (SR):** 1D Linear: 0.102 mm / 4 mils;  
Data Matrix: 0.178 mm / 7 mils; PDF417: 0.102 mm / 4 mils

### READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.  
Printing resolution, contrast, and ambient light dependent.

<b>GD4400 Standard Range (SR)</b>	<b>GD4400 High Density (HD)</b>
Code 39: 5 mils: 4.0 to 19.0 cm / 1.6 to 7.5 in	Code 39: 3 mils: 2.4 to 9.1 cm / 0.9 to 3.6 in
Code 39: 10 mils: 1.0 to 30.0 cm / 0.4 to 11.8 in	Code 39: 5 mils: 0.8 to 11.3 cm / 0.3 to 4.5 in
Data Matrix: 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in	Data Matrix: 5 mils: 2.8 to 6.1 cm / 1.1 to 2.4 in
Data Matrix: 15 mils: 0 to 23.6 cm / 0 to 9.3 in	EAN-13: 13 mils: 1.1 to 17.2 cm / 0.4 to 6.8 in
EAN-13: 13 mils: 1.5 to 40.0 cm / 0.6 to 15.7 in	PDF417: 4 mils: 1.8 to 6.8 cm / 0.7 to 2.7 in
PDF417: 10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in	PDF417: 10 mils: 0 to 14.3 cm / 0 to 5.6 in
QR Code: 10 mils: 3.0 to 12.5 cm / 1.2 to 4.9 in	QR Code: 6.7 mils: 2.1 to 4.2 cm / 0.8 to 1.7 in

### SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

ENVIRONMENTAL COMPLIANCE  
LASER CLASSIFICATION

The Quick Reference Guide for this product can be referred to for a complete list of certifications.  
Complies to China RoHS; Complies to EU RoHS  
Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

### UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge.

OPOS / JAVAPOS

JavaPOS Utilities are available for download at no charge.  
OPOS Utilities are available for download at no charge.

REMOTE HOST DOWNLOAD

Lowers service costs and improves operations.

### WARRANTY

5-Year Factory Warranty

## Accessories



### Mounts/Stands

- 11-0360 Holder, Multi-Purpose, Black
- 11-0362 Holder, Multi-Purpose, Grey
- HLD-G040-BK Desk/Wall Holder, G040, Black
- HLD-G040-WH Desk/Wall Holder, G040, White
- STD-AUTO-G040-BK Smart Stand, G040, Black
- STD-AUTO-G040-WH Smart Stand, G040, White
- STD-G040-BK Basic Stand, G040, Dark
- STD-G040-WH Basic Stand, G040, White

### GLOBAL VISION COMPANY LIMITED

Robot Tower, 308-308C Dien Bien Phu Street, Ward 4, District 3, HCMC, Vietnam

Tel: (84-8) 3818 1866 – (84-8) 3818 1972  
Email: [sales@globalvision.com.vn](mailto:sales@globalvision.com.vn)

[www.globalvision.com.vn](http://www.globalvision.com.vn)